

GPA SERIES

AC/DC Single Output: 18 - 45 Watts



Features

- Universal input 90 - 264VAC
- Wide range of output voltages
- AS60950 approval N19810
- Compact size 70 x 50 x 27mm: GPA18W
- Compact size 96 x 43 x 28mm: GPA45W
- EMI to EN55022 - C tick marked, RoHS Compliant
- Overvoltage and overload protection
- Isolation to 3000VAC
- Fully regulated output
- Output plug type 2.1 x 5.5mm Centre +VE: GPA18W
- Output plug type 2.5 x 5.5mm Centre +VE: GPA45W
- Input via two pin IEC 320 plug



MODEL	Output		Power W
	V	A	
GPA - 181DA - 03	3V	3.0A	9W
GPA - 181DA - A3	3.3V	3.0A	9W
GPA - 181DA - 05	5V	3A	15W
GPA - 181DA - 06	6V	2.8A	17W
GPA - 181DA - 09	9V	2A	18W
GPA - 181DA - 12	12V	1.5A	18W
GPA - 181DA - 15	15V	1.2A	18W
GPA - 181DA - 18	18V	1.0A	18W
GPA - 181DA - 24	24V	0.75A	18W
GPA - 451DA - 12	12V	3.8A	45W
GPA - 451DA - 15	15V	3.0A	45W
GPA - 451DA - 19	19V	2.3A	45W
GPA - 451DA - 24	24V	1.9A	45W

• Other voltages on request



The GPA & SYS1298 power supplies are available with SNAP-ON Exchangeable plugs. Connecting TIP-TIP provides Centre +VE plug.

Exchangeable plug P/N: EP-0001 = 2.1mm, EP-0002 = 2.5mm.

SYS1298 SERIES

AC/DC Single Output: 9~18 Watts



Features

- Universal input 90 - 264VAC
- Wide range of output voltages
- AS60950 approval No. N19810
- Low cost and compact size 75 x 43 x 34mm
- EMI to EN55022 - C tick marked, RoHS Compliant
- Overvoltage and overload protection
- Isolation to 3000VAC
- Fully regulated output
- Output plug type 2.1 x 5.5mm centre +VE
- Australian, US, Euro and UK plug options

MODEL	Output		Power W
	V	A	
SYS1298 - 0903 - W2A	3V	3.0A	9W
SYS1298 - 1305 - W2A	5V	2.6A	13W
SYS1298 - 1506 - W2A	6V	2.5A	15W
SYS1298 - 1509 - W2A	9V	1.7A	15W
SYS1298 - 1812 - W2A	12V	1.5A	18W
SYS1298 - 1815 - W2A	15V	1.2A	18W
SYS1298 - 1818 - W2A	18V	1.0A	18W
SYS1298 - 1824 - W2A	24V	0.75A	18W

